



SEQAGLOSS

WATER-BASED GLOSS FINISH FOR MULTI-SURFACE COATING

PRODUCT INFORMATION

PRODUCT NAME	SEQAGLOSS Water-Based Gloss and Semi-Gloss Finish for Multi-Surface Coating
DESCRIPTION	<p>SEQAGLOSS is a premium quality water-based gloss finish is an environment friendly gloss paint compared to solvent based gloss finish.</p> <p>It is environment friendly emulsion paint with APEO Free, Low VOC, Formaldehyde Free and Heavy Metals Free. This gloss paint uses technologies that can minimal environmental impact and human health problems. It is NMP free that can reduce the chemical that may be teratogenic which can cause birth defect and harmful to pregnant woman and baby in the womb.</p>
USAGE	This environment friendly gloss and semi-gloss finish is multi-surface coating for various substrates such as concrete, metal, wood, plastic, tiles, parquet floor, polycarbonate and marble. It is safe to apply for both interior and exterior surfaces for a quality and healthy life and at the same time bring glossy into your clean home.
BENEFITS	This gloss finish contains Ultra Low NMP. NMP (N-Methyl-2-Pyrrolidone) is a potential human reproductive hazard which can harm the developing fetus in pregnant woman. Sequoia Seqagloss is environment friendly that has very low NMP to minimize the side effect that may be harmful to pregnant woman and baby in the womb.
PACK SIZE	1 Litre, 5 Litres
COMPOSITION	
BINDER	Acrylic Emulsion
PIGMENT	Lightfast Non-Lead Pigments and Mineral Extenders
VOLUME SOLIDS	White 45% (nominal)
SOLUBLE	Water

PROPERTIES

TEXTURE	Water-Based Gloss and Semi-Gloss Finish
COLOUR RANGE	Refer to Sequoia colour card and SEQUOIA COLOURMIZER Fandeck
THEOROTICAL COVERAGE	Theoretical coverage which can be achieved under normal conditions is 10-12m ² /litre
DRY TIME	Touch Dry : 1 hour under normal conditions Hard dry/recoat : 3 hours under normal conditions
RECOATING INTERVAL	2-3 hours

PRE-APPLICATION

SURFACE PREPARATION Generally all surfaces to be coated must be dry, clean and sound, free of dust, dirt, grease and other contaminant

PREVIOUS PAINTED SURFACE Remove any loose or defective paint or powdery residual with a stiff bristle brush. Treat area affected by fungus with fungicidal wash solution. Fill cracks with filling putty.

RECOMMENDED PAINT SYSTEM

	Primer (1 Coat)	Finish (2Coats)
Concrete	Sequoia Wall Sealer	SEQUOIA SEQAGLOSS
Wood	Redwood Primer	
Steel	Protective Primer	

PAINT APPLICATION

THINNING For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (5%)

CLEAN UP Clean up all painting tools with clean water immediately after use

SAFETY AND PRECAUTION

- HEALTH AND SAFETY**
- Keep container tightly closed and in upright position while transport or in storage
 - Keep container and paint away from food and drinks. Keep out of reach children
 - Ensure good ventilation during application and drying. Do not breathe in vapor, use mask if required
 - Wear eye protection. In case contact with eye, rinse with plenty of water immediately and seek medical advice
 - Remove splashes from skin with soap and water
 - In case if spillage, cover spillage with sand or soil.

- ENVIRONMENT**
- Do not empty contain in container into drain, sewer system or watercourse
 - Dispose empty container according to Environment Quality Regulations

Note: The information given above is for reference only. All results are laboratory based result. Actual result may vary under different condition.