



SEQALITE

LUXURY INTERIOR WALL FINISH

EG Health Series

PRODUCT INFORMATION

PRODUCT NAME	SEQALITE Luxury Interior Wall Finish – EG Health Series
DESCRIPTION	<p>SEQALITE is a premium quality emulsion paint formulated for interior to give matt luxury finish. It is suitable for all normal interior wall and ceiling surfaces, especially for area where cleaning prerequisite like kitchen, children room and decorative use.</p> <p>It is environment friendly emulsion paint with APEO Free, Low VOC, Formaldehyde Free and Heavy Metals Free. These advanced paint technologies can minimal environmental impact and human health problems.</p>
USAGE	This environmentally friendly paint is very safe to use indoor. It very suitable for decoration and protection of interior wall, ceiling, brickwork cement board for a luxury matt finish.
BENEFITS	<p>Minimal environmental impact, Eco Green, toward create Green Home, Green Country, Green Earth.</p> <p>Safety and healthy to use for our family</p> <p>Excellent durability</p> <p>Gives a mid matt and smooth luxury surface</p> <p>Washable</p>
PACK SIZE	1 Litre, 5 Litres and 20 Litres
COMPOSITION	
BINDER	Vinyl Acetate - Acrylic copolymer
PIGMENT	Lightfast Non – pigments and Mineral Extender
VOLUME SOLIDS	White 45-50% (Nominal), other colours will vary
SOLUBLE	Water

PROPERTIES

TEXTURE	Smooth Matt Finish
COLOUR RANGE	Refer to SEQALITE colour card and SEQUOIA COLOURMIZER Fandeck
THEOROTICAL COVERAGE	Average coverage of 11-12 sq Meter/litre Actual coverage will vary according to condition of wall surfaces
DRY TIME	Touch Dry : 30-60 minutes (depend on humidity and temperature) Hard dry/recoat : 2-3 hours
RECOATING INTERVAL	2-3 hours

PRE-APPLICATION

SURFACE PREPARATION	Generally all surfaces to be coated must be dry, clean and sound, free of dust, dirt, grease and other contaminant
PREVIOUS PAINTED SURFACE	Remove any loose or defective paint or powdery residual with a stiff bristle brush. Treat area affected by fungus with fungicidal wash solution. Fill cracks with filling putty.

RECOMMENDED PAINT SYSTEM

1st coat	Primer	to paint 1 coat	SEQUOIA Wall Sealer
2nd coat & 3rd coat	Finish Coat	to paint 2 coats	SEQUOIA EG Health Series - SEQALITE Interior Wall Finish

PAINT APPLICATION

THINNING	For normal use, thinning is usually not required. If required, can add 5 – 10% of water. Note: Excessive thinning will affect the quality of the paint
CLEAN UP	Clean up all painting tools with clean water immediately after use

SAFETY AND PRECAUTION

HEALTH AND SAFETY	<ul style="list-style-type: none"> - Keep container tightly closed and in upright position while transport or in storage - Keep container and paint away from food and drinks. Keep out of reach children - Ensure good ventilation during application and drying. Do not breathe in vapor, use mask if required - Wear eye protection. In case contact with eye, rinse with plenty of water immediately and seek medical advice - Remove splashes from skin with soap and water - In case if spillage, cover spillage with sand or soil.
ENVIRONMENT	<ul style="list-style-type: none"> - Do not empty contain in container into drain, sewer system or watercourse - Dispose empty container according to Environment Quality Regulations

Note: The information given above is for reference only. All results are laboratory based result. Actual result may vary under different condition.