



SEQASHIELD

FULL ACRYLIC EXTERIOR WALL FINISH

EG Health Series

PRODUCT INFORMATION

PRODUCT NAME	SEQASHIELD Full Acrylic Exterior Wall Finish – EG Health Series
DESCRIPTION	<p>SEQASHIELD Acrylic Exterior Wall Finish is a 100% fully Acrylic premium exterior paint specially formulated with excellent weathering properties; fungus and algae resistant; excellent alkali resistant, adhesion and durability. It is formulated to provide at least 5 years protection against fungus and algae growth with correct application.</p> <p>It is environment friendly emulsion paint with APEO Free, Low VOC, Formaldehyde Free and Heavy Metals Free. These advanced paint technologies can minimal environmental impact and human health problems.</p>
USAGE	<p>This environmentally friendly paint is suitable for decoration and protection of exterior walls which is exposing to hush weather for a long lasting finish. It is safe to apply for exterior decoration and protection of wall ceiling, brickwork and cement wall for longer durability.</p>
BENEFITS	<p>Minimal environmental impact, Eco Green, toward create Green Home, Green Country, Green Earth.</p> <p>Safety and healthy to use for interior and exterior home</p> <p>Excellent durability</p> <p>Gives a mid matt and smooth luxury surface</p> <p>Washable</p>
PACK SIZE	1 Litre, 5 Litres and 20 Litres
COMPOSITION	
BINDER	100% Full Acrylic Copolymer
PIGMENT	Lightfast Non – pigments and Mineral Extender
VOLUME SOLIDS	White 45-50% (Nominal), other colours will vary
SOLUBLE	Water

PROPERTIES

TEXTURE Smooth Luxury Matt Finish

COLOUR RANGE Refer to SEQASHIELD colour card and SEQUOIA COLOURMIZER Fandeck

THEOROTICAL COVERAGE Average coverage of 12-13 sq Meter/litre
 Actual coverage will vary according to condition of wall surfaces

DRY TIME Touch Dry : 30-60 minutes (depend on humidity and temperature)
 Hard dry/recoat : 2-3 hours

RECOATING INTERVAL 2-3 hours

PRE-APPLICATION

SURFACE PREPARATION Generally all surfaces to be coated must be dry, clean and sound, free of dust, dirt, grease and other contaminant

PREVIOUS PAINTED SURFACE Remove any loose or defective paint or powdery residual with a stiff bristle brush. Treat area affected by fungus with fungicidal wash solution. Fill cracks with filling putty.

RECOMMENDED PAINT SYSTEM

1st coat	Primer	to paint 1 coat	SEQUOIA Wall Sealer
2nd coat & 3rd coat	Finish Coat	to paint 2 coats	SEQUOIA EG Health Series - SEQASHIELD Exterior Wall Finish

PAINT APPLICATION

THINNING For normal use, thinning is usually not required. If required, can add 5 – 10% of water. Note: Excessive thinning will affect the quality of the paint

CLEAN UP Clean up all painting tools with clean water immediately after use

SAFETY AND PRECAUTION

HEALTH AND SAFETY

- Keep container tightly closed and in upright position while transport or in storage
- Keep container and paint away from food and drinks. Keep out of reach children
- Ensure good ventilation during application and drying. Do not breathe in vapor, use mask if required
- Wear eye protection. In case contact with eye, rinse with plenty of water immediately and seek medical advice
- Remove splashes from skin with soap and water
- In case if spillage, cover spillage with sand or soil.

ENVIRONMENT

- Do not empty contain in container into drain, sewer system or watercourse
- Dispose empty container according to Environment Quality Regulations

Note: The information given above is for reference only. All results are laboratory based result. Actual result may vary under different condition.