



SEQUOIA PAINT®

YOUR PERSONAL TOUCH

SEQUOIA ZINC CHROMATE GREY GREEN PRIMER E7500

PRODUCT INFORMATION

PRODUCT NAME	SEQUOIA ZINC CHROMATE GREY GREEN PRIMER E7500
DESCRIPTION	This primer is a solvent based protective primer, generally designed for application on bare surface before overcoat with a finish
USAGE	Suitable for use in metal including steelwork and new metal
BENEFIT	Excellent opacity
PACK SIZE	5 litres, 20 litres
COLOUR RANGE	Grey Green

PERFORMANCE GUIDE

CHEMICAL RESISTANCE	Resistant to mild chemical fumes. Special paint systems required if surface is subject to constant chemical attack
HEAT RESISTANCE	Generally resistant to heat up to 90°C. Discolouration will occur after a prolong time is surface is constantly heated
WATER RESISTANCE	Resistant to normal atmospheric humidity present
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal condition is 9 m ² /L

PRE-APPLICATION

SURFACE PREPARATION	Generally all surfaces to be coated must be free of dust, dirt, grease and other contaminants	
PREVIOUSLY PAINTED SURFACE	Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off	
RECOMMENDED PAINT SYSTEM	Undercoat (1 coat) - Sequoia Zinc Chromate Grey Green E7500	Finish (2 Coats) - Sequoia Gloss Paint - Sequoia Protective Topcoat - Stork



SEQUOIA PAINT®

YOUR PERSONAL TOUCH

PAINT APPLICATION

THINNING	Ready for use, thinning is usually not necessary. If require thinning, add 5% of white spirit
DRY TIME	Single coat at standard thickness: 2 hours under normal conditions
CLEAN UP	Clean all equipment with white spirit immediately after use

PRODUCT DATA

COMPOSITION	Pigment : Yellow and Blue, Anti corrosive pigment Binder : Alkyd Resin Solvent : White Spirit
-------------	---

SAFETY AND PRECAUTION

HEALTH AND SAFETY	<ul style="list-style-type: none"> - Keep container tightly closed and in upright position while in transport or in storage. - Keep container and paint away from food and drinks. Keep out of reach from children. - Ensure good ventilation during application and drying. Do not breath in vapour, use mask if required - Wear eye protection. In case of contact with eye, rinse with plenty of water immediately and seek medical advice. - Remove splashes from skin with soap and water. - Flammable liquid, keep away from fire and point of ignition. In case of fire, extinguish with foam or powder fire extinguisher, sand or earth. DO NOT USE WATER. - In case of spillage, cover spillage with sand or soil - If swallowed seek medical advice immediately and show this container or label
ENVIRONMENT	<ul style="list-style-type: none"> - Do not empty contain in container into drain, sewer system or watercourses - Toxic to aquatic organism, may cause long-term effect on aquatic environment - Dispose empty container according to Environmental Quality Regulations

Note: -The information given above is for reference only.



SEQUOIA PAINT®

YOUR PERSONAL TOUCH

- All results are laboratory based result. Actual result may vary under different condition